


Description	<b>Name of fabric</b>	Twill fabric 3/2
	<b>End - Use</b>	Cleanroom
	<b>Cleanroom Class</b>	
	ISO	4 - 8
	EU GMP	A - C
	US FED Std	10 - 100.000
	<b>Weight</b>	118 g/m <sup>2</sup>
	<b>Fabric composition</b>	98% PES / 2% CA
	<b>Type of antistatic yarn</b>	Negastat P210
	<b>Finish</b>	
	<b>Weave</b>	Twill 3/2
	<b>Pattern</b>	Grid 5mm * 5mm
	<b>Sterilisation</b>	Steam - Gamma
<b>Available colors</b>		
<b>User comfort</b>	High filtration Soft feeling Very comfortable to wear	

Performance	<b>Air permeability according to ISO 9237-2 1995</b>	18,10 l/m <sup>2</sup> .s
	<b>Water vapour permeability according to ISO 11092:2014 Ret</b>	2,71 m <sup>2</sup> Pa/W
	<b>Tensile strength according to ISO 13934/1:2013</b>	Warp 830 N / Weft 1500 N
	<b>Abrasion according to ISO 12947/2:1998</b>	> 100.000 cycles
	<b>Decay time according to EN 1149-3</b>	0,01 sec
	<b>Surface resistivity according to EN 1149-1</b>	10 exp6 Ohm
	<b>Filtration effect</b>	
	by 0,3 µm	98%
by 0,5 µm	98%	
by 1 µm	98%	